

Evacuation Slyde

 belluscura™



- **Folds flat and stacks for easy storage**
- **Restraints with the buckles to secure the patient for transport**
- **Corrugated polypropylene, double-wall construction is lightweight and durable**
- **Strong web handles at corners and sides provide multi-point control for two to seven carriers**
- **The length of the web handle allows an ergonomically correct upright posture for operators during stair descent**

500lb
Capacity

1 YEAR
Warranty



The Belluscura Evacuation Slyde provides a safe, efficient way to evacuate non-ambulatory patients from any multistory building using the stairways. It folds up and stores in stacks up to five units in a storage sleeve. The sleeve can be wall-mounted for quick access in key locations.


Evacuation Slyde



Features and Benefits

- Functions as post-evacuation surge capacity device
- Lightweight for easier transports
- Buckle restraints are quick and easy to use¹
- Compatible with Belluscura Stairwell Belay System for heavy patient evacuations
- Wall-mounted storage options are space-saving and convenient
- Folds flat and stacks 5 deep for easy storage
- Easy set-up and instruction pictograms on each unit
- Four strong web handles for multi point control by 2 to 7 operators
- Size permits continued stairwell traffic flow during patient evacuation


Accessories




Belay Box and Bolt
6400-030-000



Provides stable wall anchor



Stairwell Belay
6400-020-000



5 COUNT
6400-010-000

Slyde Sleeve

Specifications

Model Number	6400-000-000
Material	Corrugated polypropylene
Height	8 in. (20.3 cm)
Width²	19 in. (48.3 cm)
Length	85 in. (215.9 cm)
Weight	9 lb. (4.1 kg)
Folded Height	2 in. (5.1 cm)
Max. Weight Capacity^{3,4}	500 lb. (227 kg)

www.belluscura.com

Belluscura, Ltd.
Oxford Center for Innovation
New Road, Oxford OX1 1BY
United Kingdom
tel: +44 (0) 1865 261506

Belluscura, LLC.
15455 Dallas Parkway
Suite 600
Addison, TX 75001
tel: 1-786-703-7996
toll free: 1-844-883-0940

- 1 Passenger restraint set includes waist and chest restraints.
- 2 Dimensions are measured from the outermost edges of the main frame. Specifications are rounded to the nearest whole number. Conversions are calculated before rounding.
- 3 Operators must consider the weight of the passenger, equipment and accessories when determining the total weight on the product.
- 4 Maximum weight capacity is total weight distributed in accordance with basic human anatomy. Belluscura reserves the right to change specifications without notice.