

# EVACUATION SLYDE®



The DQE Evacuation Slyde provides a safe, efficient way to evacuate non-ambulatory occupants from any multi-story building using the stairways. It folds flat and stores in stacks of up to five units in a storage sleeve. The sleeve can be wall-mounted for quick access in key locations.

# DQE®

Ready now for what's next.™

- Folds flat and stacks for easy storage
- Restraints with buckles to secure the occupant for transport
- Corrugated polypropylene, double-wall construction is lightweight and durable
- Strong web handles at corners and sides provide multi-point control for two to seven carriers
- The length of the web handle allows an ergonomically correct upright posture for operators during stair descent.



# EVACUATION SLYDE®

# DQE®

Ready now for what's next.™

## FEATURES & BENEFITS

- Folds flat and stacks 5 deep for easy storage
- Easy set-up and instruction pictograms on each unit
- Four strong web handles for multi-point control by 2 to 7 operators
- Size permits continued stairwell traffic flow during occupant evacuation
- Functions as post-evacuation surge capacity device
- Lightweight for easier transports
- Chest and waist buckle restraints are quick and easy to use
- Compatible with Stairwell Belay System for heavy occupant evacuations
- Wall-mounted storage options are space-saving and convenient

## ACCESSORIES



Stairwell Belay Storage Box (IC5031)



Belay System provides a stable wall anchor



Stairwell Belay System (IC5030)

Standard Sleeve (IC5011)

Bariatric Sleeve (IC5021)



Storage Sleeve

## EVACUATION SLYDE MODELS

- Standard Slyde (IC5010)
- Standard Slyde - 5 pack with Storage Sleeve (IC5105)
- Bariatric Slyde (IC5020)
- Bariatric Slyde - 5 pack with Storage Sleeve (IC5205)

## SPECIFICATIONS

Material: Corrugated polypropylene

Height: 8" (20.3 cm)

Folded Height: 2" (5.1 cm)

Width<sup>1</sup>: Standard - 17" (43.18 cm);  
Bariatric - 21" (53.34 cm)

Length: 82" (215.9 cm)

Weight: Standard - 9 lb (4.1 kg);  
Bariatric - 11 lb (5.9 kg)

Maximum Weight Capacity<sup>2,3</sup>:  
Standard - 400 lb (600 kg);  
Bariatric - 600 lb (272 kg)

## CONTACT US

DQE Inc.  
[www.EvacuationSlyde.com](http://www.EvacuationSlyde.com)  
[info@dqeready.com](mailto:info@dqeready.com)  
800-355-4628

<sup>1</sup>Dimensions are measured from the outermost edges of the main frame. Specifications are rounded to the nearest whole number. Conversions are calculated before rounding.

<sup>2</sup>Operators must consider the weight of the passenger, equipment and accessories when determining the total weight of the product.

<sup>3</sup>Maximum weight capacity is total weight distributed in accordance with basic human anatomy. DQE reserves the right to change specifications without notice.